

**Amendments to the Claims:**

Please cancel claim 1 without prejudice or disclaimer.

This listing of claims replaces and supersedes all prior listings of claims in the application:

1. (Cancelled)
2. (Currently Amended) Device pursuant to claim 4 13, characterized in that  
the transverse yoke (3) and the limbs (4A, 4B) of the roll bar (2) are designed as a single piece.
3. (Currently Amended) Device pursuant to claim 4 13, characterized in that  
the synchronizing device (17) is provided with a synchronization shaft (20) that is mounted fixedly parallelly to the transverse yoke (3) and is connected to each of the limbs (4A, 4B) by means of a tooth profile (21) that meshes with a notched strip (22) that is arranged on the assigned limb (4A, 4B).
4. (Currently Amended) Device pursuant to claim 4 13, characterized in that  
the central retaining and activating device (12) is arranged in a cross bar (13, 13') that stretches essentially parallelly to the transverse yoke (3) of the roll bar (2) in the installation position above the loading opening (11).

5. (Currently Amended) Device pursuant to claim 4 13, characterized in that

the central retaining and activating device (12) comprises a retaining plate (19) that is arranged on the roll bar (2) in an area which is at least nearly the center of the width of the vehicle and that is in mesh with a fixedly mounted engaging element in the non-operational position of the roll bar (2).

6. (Original) Device pursuant to claim 5, characterized in that

the central retaining and activating device (12) comprises an engaging element that is fixedly mounted on the cross bar (13, 13') and that is controlled by the actuator (18) and is in mesh with the roll bar (2) in the non-operational position of the latter.

7. (Currently Amended) Device pursuant to claim 4 13, further comprising:

~~characterized in that~~

a spring drive mechanism is provided as the drive in order to transfer the roll bar out of a non-operational position into a raised supporting position, whereby said spring drive mechanism comprises at least one compression spring that acts on one limb of the roll bar and is compressed in the non-operational position of the roll bar.

8. (Currently Amended) Device pursuant to claim 3, further comprising: ~~characterized~~

~~in that~~

a drive element (23) is provided as a drive in order to transfer the roll bar (2) out of a non-operational position into a raised supporting position, whereby said drive element engages at the synchronization shaft (20).

9. (Original) Device pursuant to claim 8, characterized in that

the drive element is a spring (23) that is pre-stressed in a twisted form in the non-operational position of the roll bar (2) between the synchronization shaft (20) and a fixed point (24) and sets the synchronization shaft (20) in rotation when the roll bar (2) is released.

10. (Previously Presented) Device pursuant to claim 4, characterized in that

the cross bar (13, 13') is arranged between fixedly held guiding devices (6; 7) of the limbs (4A, 4B) of the roll bar (2).

11. (Currently Amended) Device pursuant to claim 4, characterized in that

the cross bar (13, 13'), the guiding devices (6, 7, 8) connected to the ~~former~~ cross bar, and the roll bar (2) form a pre-mountable module.

12. (Original) Device pursuant to claim 11, characterized in that

the pre-mountable module comprises a torsion profile (15) that extends in the vehicle transverse direction in the installation position above the loading opening (11) and can be connected tightly to the vehicle body whereby the roll bar (2) is inserted through said torsion profile in the pre-assembled state.

13. (New) Roll-over protection device for a motor vehicle, said device comprising:

a roll bar (2) provided with an at least nearly U-shaped design having a transverse yoke (3) and lateral limbs (4A, 4B) leaving a loading opening (11) unobstructed and extending to span substantially the width of the vehicle, the lateral limbs (4A, 4B) being displaceable along fixed guiding devices (6, 7, 8) in order to transfer the roll bar (2) out of a lowered non-operational position into a raised supporting position;

a central retaining and activating device (12) for the roll bar (2), said central retaining and activating device (12) being controlled by an actuator (18); and

a synchronizing device (17) connected to both limbs (4A, 4B) of the roll bar (2) to synchronize the displacement of the limbs (4A, 4B) along the guiding devices (6, 7, 8).